



POWER UNIT SUPPLY FOR 3 x XENON STROBE LIGHT P/N 6480502

MAIN FEATURES - Aviation Strobe Light Power Supply CS25 Certified (Dassault Aviation) Replacement of P/N 60-2038 (HOSKINS)

- **High reliability:** 5 000 H
- **Low weight**
- **Resistance to high vibrations**
- **Tested for extreme environment**

Dassault Aviation EGS / DGT-DTF/SYS/AV 69706

TECHNICAL FEATURES

- **Input voltage:** 28VDC- DO160D cat Z
- **Input current:** 1.5 A
- **Input power:** 42 W
- **Rating:** 0.75 Hz
- **Output voltage:** 365 V
- **Output energy:** 3 x 10 joules
- **Operating Temperature :** -55°C / +70°C

• Connecting:

- **Input:** +V: 230 mm red wire with 320555 terminal
0V: on casing

• Output:

3 x output with MS3102E10SL3P connector

Arrangement :

A	=	+ HT
B	=	Excit
C	=	- HT

- **Altitude :** + 55000 ft

- **Weight :** 1100 grs (2.42 lbs)

CONTACTS

- **Phone:** +33 (0)380 356 390,

- **Email:** jpc@jpcaviation.com

- **Website:** www.jpcaviation.com

